



形式	寸法																				アーマチュアハブとロータハブの標準軸穴径部寸法				Y-Z	Oリング有無 ドライブピン の本数	標準か非標準							
	A	AD	AH	B	D	DP	E	F	RD	G	H	J	JD	L	KL	SL	M	MP	N	P	Q	R	S1H7	U1 ^{+0.1}				W1F7	—	S2H7	U2 ^{+0.1}	W2F7	C	
HMC-W100	12.5	165	63	100	262	133.4	2	14.3	70	0.7	73	260.2	209.5	137.7	1000	4.7	45.8	15.7	15	156	M10	62	42	3.5	12	—	42	3.5	12	1.5	6-M8	無し	3	非標準品
																							—	—	—	—								
HMC-W120	13.7	185	65.3	105	319.5	149.3	2	14.1	85	1.0	74	322.3	247.6	140.5	1000	6	54.6	5.9	15	182	M10	62.5	50	3.5	12	—	50	3.5	12	1.5	6-M8	無し	4	標準品
																							—	—	—	—								
HMC-W150	13.7	250	78.3	150	393.7	215.9	1	16.4	100	1.0	85	397.7	330.2	157	1000	8	55.4	8.6	20	248	M12	65	60	5	15	—	60	5	15	2	6-M8	無し	4	標準品
																							—	—	—	—								